



表8：LFDTM, MLFDTMシリーズ寸法表

スタンダード		主要寸法 (mm)											玉 列 数	質 量 (kg)	基本定格荷重		動許容モーメント M (N・m)												
標準型 両シール付 Bシリーズ(UU)	防錆型 両シール付 Mシリーズ(UU)	d	D	L	Df	T	t	Dp	S	A	B	C			Co	M													
LFDTM6-UU	MLFDTM6-UU	6	12 15 19 21 23 28	35	28	18	5	20	M3	—	—	4	0.024	354	310	1.5													
LFDTM8-UU	MLFDTM8-UU	8															45	32	21	5	24	M3	—	—	4	0.05	419	450	2.0
LFDTM10-UU	MLFDTM10-UU	10															55	39	25	6	29	M4	—	—	4	0.08	865	850	6.5
LFDTM12-UU	MLFDTM12-UU	12															57	42	27	6	32	M4	—	—	4	0.10	892	860	7.1
LFDTM13-UU	MLFDTM13-UU	13															60	43	29	6	33	M4	—	—	4	0.11	902	870	7.6
LFDTM16B-UU	MLFDTM16B-UU	16															68	48	34	6	—	M4	31	22	5	0.18	1248	1300	11.3
LFDTM20B-UU	MLFDTM20B-UU	20	80	54	38	8	—	M5	36	24	5	0.24	2083	2020	23.8														
LFDTM25B-UU	MLFDTM25B-UU	25	112	62	46	8	—	M5	40	32	6	0.48	3517	3570	51.4														
LFDTM30B-UU	MLFDTM30B-UU	30	122	74	51	10	—	M6	49	35	6	0.64	5273	5010	85.6														
LFDTM35B-UU	MLFDTM35B-UU	35	134	82	60	10	—	M6	55	38	6	0.90	5722	6180	102.5														
LFDTM40B-UU	MLFDTM40B-UU	40	153	96	70	13	—	M8	64	45	6	1.88	7872	8070	171.4														

