# Magnetic Field Resistant 2-Color Indicator Solid State Auto Switch

D-P3DWASC/D-P3DWASE ( € c Tu) us

(Electrical Entry: Pre-wired connector)

- It is possible to use in an environment which generates a magnetic field disturbance (AC magnetic field).
- The proper operating range can be determined by the color of the light. (Red → Green ← Red)



### **∕**\Caution

#### **Precautions**

For single-phase AC welding machines. If it is used for current inverter welders (including rectifying type) and condenser type welders, the magnetic field resistance is reduced. Please contact SMC regarding the performance.

## **Magnetic Field Resistance**

If the current of the AC welding machine is 16000 A or lower, the auto switch can be used, even if the distance between the welding conductor (gun cable) and the cylinder/actuator or auto switch is 0 mm.

Please contact SMC when the AC welding current exceeds 16000 A.

Weight	(g)
	(9)

Auto switch model		D-P3DWASC	D-P3DWASE
Lead wire length (m)	0.3	2	5



Connector pin

Model	Cor	nector pin and wiring		
Wodel	1	2	3	4
D-P3DWASC	_	_	OUT(∓)	OUT(±)
D-P3DWASE	OUT(±)	_	_	OUT(∓)

# **Auto Switch Specifications**

Refer to SMC website for the details of the products conforming to the international standards

PLC: Programmable Logic Controller

D-P3DWASC/E (With indicator light)			
Auto switch model	D-P3DWASC D-P3DWASE		
Applicable load	24 VDC relay, PLC		
Load voltage	24 VDC		
Load current	6 to 40 mA		
Internal voltage drop	5 V or less		
Leakage current	1 mA or less at 24 VDC		
Operating time	40 ms or less		
Indicator light	Operating range Red LED illuminates. Proper operating range Green LED illuminates.		
Standard	CE marking, UL (CSA), RoHS		


Oilproof Heavy-duty Lead Wire Specifications


Auto switch model		D-P3DWASC D-P3DWASE	
Sheath	Outside diameter [mm]	ø4.8	
Insulator	Number of cores	2 cores	
insulator	Outside diameter [mm]	ø1.52	
0	Effective area [mm²]	0.5	
Conductor	Strand diameter [mm]	m) ø0.08	
Minimum bending radius [mm] (Reference values)		29	

- Impact resistance Switch: 1000 m/s², Connector: 300 m/s²
- ullet Insulation resistance 50 M $\Omega$  or more at 500 VDC Mega (between lead wire and case)
- Withstand voltage 1000 VAC for 1 minute (between lead wire and case)
- Ambient temperature -10 to 60°C
- Enclosure IEC60529 standard IP67
   Polarity: Non-polar

### **Dimensions**

(mm)





Note) A white color heat shrink tube is attached to the D-P3DWASE type only.

