



Miniature Through/Ground Conductor and Ex Terminal Blocks 2.5 mm² for DIN 35 Rail 264 Series

CAGE CLAMP®

0.08 ... 2.5 mm ² 800 V/8 kV/3 ① I _N 24 A	AWG 28 ... 12 * 300 V, 20 A ② 600 V, 20 A ③	0.08 ... 2.5 mm ² 800 V/8 kV/3 ① I _N 24 A	AWG 28 ... 12 * 300 V, 20 A ② 600 V, 20 A ③
Terminal block width 6 mm / 0.236 in.  8 ... 9 mm / 0.33 in. ②		Terminal block width 10 mm / 0.394 in.  8 ... 9 mm / 0.33 in. ②	



* AWG 12: THHN, THWN

① 800 V = rated voltage
8 kV = rated surge voltage
3 = pollution degree
(also see Section 14)


② Strip length, see packaging or instructions.

③ Suitable for Ex i applications

④ Suitable for Ex e II applications
0.5 mm² ... 2.5 mm²/AWG 20 ... 12*
690 V, 23 A
(also see Section 14)

⑤ See application notes for:
Test plug module, page 416
Alternate comb-style jumper bar, page 294

Item No.	Pack. Unit	Item No.	Pack. Unit	264 Series Accessories	
2-conductor miniature through terminal block, for DIN 35 rail		4-conductor miniature through terminal block, for DIN 35 rail		Miniature WSB (see Section 13)	
 gray	264-711 100	 gray	264-731 100	End and intermediate plate, 4 mm thick	
 blue	264-714 ③ 100	 blue	264-734 ③ 100	 orange	264-369 25
 orange	264-716 100	 orange	264-736 100	 gray	264-368 25
 light gray ⑤	264-125 ④ 100	 light gray ⑤	264-225 ④ 100	 light gray	264-370 25
Item-Specific Accessories		Item-Specific Accessories		Ex e/Ex i separator, orange, 4 mm thick	
Alternate comb-style jumper bar, ⑤ insulated, I _N = I _N terminal block		Alternate comb-style jumper bar, ⑤ insulated, I _N = I _N terminal block		 66 mm	264-367 25
2-way	281-492 100 (4x25)	2-way	280-492 200 (8x25)	Comb-style jumper bar, insulated, I_N 16 A, gray, reduces maximum conductor size to 1.5 mm ² /AWG 16	
Test plug module, ⑤ can be snapped together, 6 mm wide		Test plug module, ⑤ can be snapped together, 10 mm wide		 2-way	264-402 200 (8x25)
gray	249-136 100 (4x25)	gray	249-139 100 (4x25)	Operating tool, of insulating material	



Item No.	Pack. Unit	Item No.	Pack. Unit	Item No.	Pack. Unit
4-conductor miniature ground conductor terminal block, for DIN 35 rail		Item-Specific Accessories		264 Series Accessories	
 green-yellow	264-737 100	Alternate comb-style jumper bar, ⑤ insulated, I _N = I _N terminal block		Test plug, with 500 mm cable, 2 mm Ø	
 green-yellow ⑤	264-737/999-950 ④ 100	2-way	280-492 200 (8x25)	 red	210-136 50
Item-Specific Accessories		Test plug module, ⑤ can be snapped together, 10 mm wide		Test plug, with 500 mm cable, 2.3 mm Ø	
Alternate comb-style jumper bar, ⑤ insulated, I _N = I _N terminal block		gray	249-139 100 (4x25)	 yellow	210-137 50
Test plug module, ⑤ can be snapped together, 10 mm wide		Miniature WSB Quick marking system, 10 strips with 10 markers per card, 5 mm wide markers		Miniature WSB Quick marking system, 10 strips with 10 markers per card, 5 mm wide markers	
gray	249-139 100 (4x25)	Test plug module, ⑤ can be snapped together, 10 mm wide		plain	248-501 5
Item-Specific Accessories		Test plug module, ⑤ can be snapped together, 10 mm wide		Screwless end stop, for DIN 35 rail, 6 mm wide	
Alternate comb-style jumper bar, ⑤ insulated, I _N = I _N terminal block		Test plug module, ⑤ can be snapped together, 10 mm wide		 gray	249-116 100 (4x25)
Test plug module, ⑤ can be snapped together, 10 mm wide		Test plug module, ⑤ can be snapped together, 10 mm wide		Screwless end stop, for DIN 35 rail, 10 mm wide	
gray	249-139 100 (4x25)	Test plug module, ⑤ can be snapped together, 10 mm wide		 gray	249-117 50 (2x25)
Item-Specific Accessories		Test plug module, ⑤ can be snapped together, 10 mm wide		Steel carrier rail, acc. to EN 60715, 35 x 7.5 mm, 1 mm, 2 m/6'6" long	
Alternate comb-style jumper bar, ⑤ insulated, I _N = I _N terminal block		Test plug module, ⑤ can be snapped together, 10 mm wide		slotted	210-112 10 (10x1)
Test plug module, ⑤ can be snapped together, 10 mm wide		Test plug module, ⑤ can be snapped together, 10 mm wide		Steel carrier rail, acc. to EN 60715, 35 x 7.5 mm, 1 mm, 2 m/6'6" long	
gray	249-139 100 (4x25)	Test plug module, ⑤ can be snapped together, 10 mm wide		unslotted	210-113 10
Item-Specific Accessories		Test plug module, ⑤ can be snapped together, 10 mm wide		Aluminum carrier rail, acc. to EN 60715, 35 x 8.2 mm, 1.6 mm, 2 m/6'6" long	
Alternate comb-style jumper bar, ⑤ insulated, I _N = I _N terminal block		Test plug module, ⑤ can be snapped together, 10 mm wide		unslotted	210-196 10
Test plug module, ⑤ can be snapped together, 10 mm wide		Test plug module, ⑤ can be snapped together, 10 mm wide		Aluminum carrier rail, acc. to EN 60715, 35 x 8.2 mm, 1.6 mm, 2 m/6'6" long	
gray	249-139 100 (4x25)	Test plug module, ⑤ can be snapped together, 10 mm wide		Aluminum carrier rail, acc. to EN 60715, 35 x 8.2 mm, 1.6 mm, 2 m/6'6" long	