Miniature Through/Ground Conductor and Ex Terminal Blocks 2.5 mm² for DIN 15 Rail 264 Series

0.08 ... 2.5 mm² 800 V/8 kV/3 ❶ I_N 24 A AWG 28 ... 12 * 300 V, 20 A 600 V, 20 A Terminal block width 6 mm / 0.236 in. 8 ... 9 mm / 0.33 in. ❷	0.08 ... 2.5 mm² 800 V/8 kV/3 ❶ I_N 24 A AWG 28 ... 12 * 300 V, 20 A 600 V, 20 A Terminal block width 10 mm / 0.394 in. 8 ... 9 mm / 0.33 in. ❷

* AWG 12: THHN, THWN

❶ 800 V = rated voltage
8 kV = rated surge voltage
3 = pollution degree
(also see Section 14)

❷ Strip length, see packaging or instructions.

❸ Suitable for Ex i applications

❹ Suitable for Ex e II applications
0.5 mm² ... 2.5 mm²/AWG 20 ... 12*
690 V, 23 A
(also see Section 14)

❺ See application notes for:
Test plug module, page 416
Alternate comb-style jumper bar, page 294





	Item No.	Pack. Unit
2-conductor miniature through terminal block, for DIN 15 rail		
gray	**264-701**	100
blue	**264-704** ❸	100
orange	**264-706**	100
light gray	**264-120** ❹	100

	Item No.	Pack. Unit
4-conductor miniature through terminal block, for DIN 15 rail		
gray	**264-721**	100
blue	**264-724** ❸	100
orange	**264-726**	100
light gray	**264-220** ❹	100

Item-Specific Accessories

Alternate comb-style jumper bar, ❺ insulated, $I_N = I_N$ terminal block
2-way **281-492** 100 (4x25)

Test plug module, ❺ can be snapped together, 6 mm wide
gray **249-136** 100 (4x25)

Item-Specific Accessories

Alternate comb-style jumper bar, ❺ insulated, $I_N = I_N$ terminal block
2-way **280-492** 200 (8x25)

Test plug module, ❺ can be snapped together, 10 mm wide
gray **249-139** 100 (4x25)



	Item No.	Pack. Unit
4-conductor miniature ground conductor terminal block, for DIN 15 rail		
green-yellow	**264-727**	100
green-yellow	**264-727/999-950** ❹	100

Item-Specific Accessories

Alternate comb-style jumper bar, ❺ insulated, $I_N = I_N$ terminal block
2-way **280-492** 200 (8x25)

Test plug module, ❺ can be snapped together, 10 mm wide
gray **249-139** 100 (4x25)

264 Series Accessories

Miniature WSB
(see Section 13)

End and intermediate plate, 4 mm thick
orange **264-369** 25
gray **264-368** 25
light gray **264-370** 25

Ex e/Ex i separator, orange, 4 mm thick
66 mm **264-367** 25

Comb-style jumper bar, insulated, I_N 16 A, gray, reduces maximum conductor size to 1.5 mm²/AWG 16
2-way **264-402** 200 (8x25)

Operating tool, of insulating material
2-way **280-432** 1

Test plug, with 500 mm cable, 2 mm Ø
red **210-136** 50

Test plug, with 500 mm cable, 2.3 mm Ø
yellow **210-137** 50

Miniature WSB Quick marking system, 10 strips with 10 markers per card, 5 mm wide markers
plain **248-501** 5

Screwless end stop, for DIN 15 rail, 6 mm wide
gray **249-101** 25

Steel carrier rail, acc. to EN 60715, 15 x 5.5 mm, 1 mm, 2 m/6'6" long
slotted **210-111** 1

Steel carrier rail, acc. to EN 60715, 15 x 5.5 mm, 1 mm, 2 m/6'6" long
unslotted **210-295** 1

Aluminum carrier rail, acc. to EN 60715, 15 x 5.5 mm, 1 mm, 2 m/6'6" long
unslotted **210-296** 10

Operating tool, of insulating material
1-way **209-130** 1

Certification organizations can be found in the overview on page 622.