


Extruded Brackets - For 1 Slot


For 8 Series (Slot Width 10mm) Aluminum Extrusions



Features: Extruded Brackets with Unequal Sides. Effective when strength is required in narrow clearances between extrusions.

Scalene Brackets

HBLTF8




MMaterial: A6N01SS-T5
SSurface Treatment: Anodize

Part Number	Mass (g)	Applicable Screw, T Nut			Allowable Load (N)	Unit Price (1-99 pc(s))	Volume Discount Rate (100-200)
		Screw	Quantity	T Nut			
HBLTF8	90	CBM8-20	3	HNTT8-8	3	2572	




Example



Features: Numbers of screws are the same as HBLTS8. Extrusions can be connected more securely.

Ultra Thick Brackets

HBLUS8 HBLUSB8 (Black Anodize)



Type	M Material	S Surface Treatment
HBLUS8	A6N01SS-T5	Anodize
HBLUSB8		Black Anodize


Part Number	Mass (g)	Applicable Screw, T Nut			Allowable Load (N)	Unit Price (1-99 pc(s))	Volume Discount Rate (100-200)
		Screw	Quantity	T Nut			
HBLUS8	151	CBM8-25	2	HNTT8-8	2	2058	
HBLUSB8* (Black Anodize)							

* For repairing black anodizing, refer to P.846.


Features: Numbers of screws are the same as HBKTS8. Extrusions can be connected more securely. Perpendicularly Machined.

Ultra Thick Brackets (Perpendicularly Machined)

HBKUS8 HBKUSB8 (Black Anodize) Perpendicularity K: 0.06



There are protrusions on the bracket bottom to be inserted into aluminum extrusion slots.



Type	M Material	S Surface Treatment
HBKUS8	A6N01SS-T5	Anodize
HBKUSB8		Black Anodize

Part Number	Mass (g)	Applicable Screw, T Nut			Allowable Load (N)	Unit Price (1-99 pc(s))	Volume Discount Rate (100-200)
		Screw	Quantity	T Nut			
HBKUS8	151	CBM8-25	2	HNTT8-8	2	2058	
HBKUSB8* (Black Anodize)							

* For repairing black anodizing, refer to P.846.